

**MATERIAL SAFETY DATA SHEET**

**PRODUCT NAME:** CRUISER RED CORDURITE  
**PRODUCT CODE:** 104-012

**HMS CODES:** H F R P  
2\* 3 0 G

===== **SECTION I - MANUFACTURER IDENTIFICATION** =====

**MANUFACTURER'S NAME:** The Simpson Coatings Group, Inc.  
**ADDRESS:** 111 SOUTH MAPLE AVENUE, SO. S.F., CA 94080  
**EMERGENCY PHONE:** 1-800-424-9300 **INFORMATION PHONE:** 650-873-5990  
**DATE REVISED :** 01-19-01 **NAME OF PREPARER :** TIM SIMPSON  
**REASON REVISED :** ANNUAL REVISION

===== **SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION** =====

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		OSHA/PEL	ACGIH/TLV	OTHER		
ETHYL 3-ETHOXYPROPIONATE	763-69-6	N/R	N/R	N/R	1.1 77F	15
*LEAD CHROMATE LEAD SULFATE, YELLOW	1344-37-2	.05MG/M3	.05MG/M3		N/A	11.34
2-HEPTANONE	110-43-0	100 PPM	50 PPM		2.1 68F	5
*MIXED XYLENES	1330-20-7	100 PPM	100 PPM		5.1 68F	1
*1-BUTANOL	71-36-3	50 PPM	50 PPM		4.4 68F	6

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.  
**WARNING! THIS PRODUCT CONTAINS CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.**

===== **SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS** =====

**BOILING RANGE:** 243 to 329 Deg F **SPECIFIC GRAVITY (H2O=1):** 1.2  
**VAPOR DENSITY:** HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER  
**COATING V.O.C. :** 3.27 LB/GL ( 392 G/L)  
**MATERIAL V.O.C.:** 3.27 LB/GL ( 392 G/L)  
**SOLUBILITY IN WATER:** INSOLUBLE  
**APPEARANCE AND ODOR:** VISCOUS LIQUID WITH HYDROCARBON SOLVENT ODOR

===== **SECTION IV - FIRE AND EXPLOSION HAZARD DATA** =====

**FLASH POINT:** 80 Deg F **METHOD USED:** TCC  
**FLAMMABLE LIMITS IN AIR BY VOLUME--** LOWER: 1.0% UPPER: 11.2%

**EXTINGUISHING MEDIA:** FOAM, CO2, DRY CHEMICAL, WATER FOG

**SPECIAL FIREFIGHTING PROCEDURES**

FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS. FIGHT AS VOLATILE LIQUID FIRE USE WATER TO COOL FIRE-EXPOSED CONTAINERS. AVOID SPREADING FIRE WITH COOLING WATER. FOG NOZZLES FOR WATER IS RECOMMENDED.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY BE MOVED BY VENTILATION OR TRAVEL ON THE GROUND TO DISTANT SOURCES OF IGNITION. ISOLATE FROM ALL SOURCES OF HEAT. EMPTY CONTAINERS MAY EXPLODE DUE TO RESIDUES. OBSERVE THIS MSDS FOR EMPTIED CONTAINER HANDLING. ALL METAL CONTAINERS MUST BE BONDED AND/OR GROUNDED DURING LIQUID TRANSFER.

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE  
CONDITIONS TO AVOID**

AVOID PROLONGED BREATHING OF VAPORS, SKIN OR EYE CONTACT. STORE AWAY FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, OPEN FLAME

**INCOMPATIBILITY (MATERIALS TO AVOID)**

AVOID STRONG OXIDIZING AGENTS, ACIDS AND BASES.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

CARBON DIOXIDE, CARBON MONOXIDE, OTHER DIOXIDES, TOXIC FUMES AND SMOKE.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR**

## ===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

DIZZINESS, NAUSEA, HEADACHE, IRRITATION OF THE RESPIRATORY TRACT, VOMITING, UNCONSCIOUSNESS OR EVEN ASPHIXIATION. PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO THE SOLVENTS MAY LEAD TO PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

SKIN: IRRITATION, DRYING OR CRACKING AND DEFATTING.

EYES: IRRITATION OF THE EYES, WATERING, BLURRED VISION.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

SEVERE IRRITATION OR BURNING SENSATION. CRACKING AND DEFATTING ACTION MAY OCCUR.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

DIZZINESS, NAUSEA, IRRITATION OF THE GASTROINTESTINAL TRACT AND VOMITING. THIS PRODUCT HAS ANESTHETIC EFFECTS CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT WITH HEADACHE, NAUSEA, DIZZINESS, UNCONSCIOUSNESS OR COMA.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

EXCESSIVE CHRONIC EXPOSURE TO LEAD/CHROMIUM COMPOUNDS MAY CAUSE A METALLIC TASTE IN THE MOUTH, LOSS OF APPETITE, CONSTIPATION, ABDOMINAL CRAMPS, SLEEPLESSNESS OR WEAKNESS. CHROMIUM COMPOUNDS ARE CARCINOGENS. LEAD COMPOUNDS, WHEN INGESTED HAVE A CUMULATIVE TOXIC EFFECT, WHEN AMOUNTS INGESTED EXCEED THE LEVEL IN WHICH THE BODY CAN NORMALLY ELIMINATE. PRODUCT CONTAINS CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

**CARCINOGENICITY: NTP? YES IARC MONOGRAPHS? YES OSHA REGULATED? YES**

LEAD COMPOUNDS ARE OSHA SPECIFICALLY REGULATED (29 CFR 1910) AND CHROMIUM COMPOUNDS ARE NTP AND IARC HUMAN CARCINOGENS.

LEAD CHROMATE PIGMENT CONTAINS 60% BY WT. AS LEAD COMPOUNDS AND 13% BY WT. AS CHROMIUM COMPOUNDS, A HUMAN CARCINOGEN.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

PRE-EXISTING HEART, LUNG, KIDNEY, LIVER, SKIN DISORDERS

**EMERGENCY AND FIRST AID PROCEDURES**

INHALATION: REMOVE FROM EXPOSURE, RESTORE BREATHING, CONSULT PHYSICIAN.

EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MIN. WITH EYELIDS OPEN. CONSULT PHYSICIAN IMMEDIATELY.

SKIN CONTACT: WASH WITH SOAP AND WATER., REMOVE CONTAMINATED CLOTHING.

INGESTION: DO NOT INDUCE VOMITING. DRINK ONE TO TWO GLASSES OF WATER TO DILUTE. SEEK MEDICAL ASSISTANCE IMMEDIATELY.

=====  
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE  
=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CONTAIN AND REMOVE WITH INERT ABSORBANT AND NON-SPARKING TOOLS. WEAR PRETECTIVE EQUIPMENT DURING CLEANUP. CONTAIN LIQUID TO PREVENT CONTAINMENT OR SOIL AND GROUND WATER.

**WASTE DISPOSAL METHOD**

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

KEEP CLOSURE TIGHT AND CONTAINER IN UPRIGHT POSITION. STORE AWAY FROM HEAT OR OTHER SOURCES OF IGNITION. CONTAINERS MUST BE GROUNDED AND/OR BONDED DURING LIQUID TRANSFER. EMPTIED CONTAINERS MAY STILL CONTAIN HAZARDOUS MATERIALS THIS MSDS MUST BE OBSERVED WHEN HANDLING THEM.

**OTHER PRECAUTIONS**

THIS PRODUCT MAY CONTAIN LESS THAN 1% BY WEIGHT OF THE FLOWING COMPOUNDS:ETHANOL(CAS#67-17-5),METHANOL(CAS#67-56-1). BENZENE, A CANCER CAUSING AROMATIC COMPOUND OCCURS IN ALL PETROLEUM PRODUCTS ESPECIALLY AROMATIC SOLVENTS AS AN IMPURITY. THIS PRODUCT ALSO CONTAINS LESS THAN 0.1% BY WEIGHT OF CRYSTALLINE SILICA(CAS#14464-46-1) WHICH HAS A LIMITED CARCINOGENICITY ON HUMANS AND CADMIUM(CAS#7440-43-9) WHICH IS A NTP ANTICIPATED HUMAN CARCINOGEN AND AN IARC PROBABLE HUMAN CARCINOGEN. MAY CONTAIN LESS THAN 1% COBALT, MANGANESE, AND ZINC COMPOUNDS( CATRGORY CODES: N096,N450,N982).

=====  
SECTION VIII - CONTROL MEASURES  
=====**RESPIRATORY PROTECTION**

APPROVED CHEMICAL MECHANICAL FILTER RESPIRATOR

**VENTILATION**

REQUIRED, 200 CFM MINIMUM.

**PROTECTIVE GLOVES**

CHEMICALLY RESISTANT PLASTIC OR RUBBER.

**EYE PROTECTION**

SAFETY EYEWEAR WITH SIDE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

EYE WASH AND SAFETY SHOWERS IN WORK AREA ARE RECOMMENDED.

**WORK/HYGIENIC PRACTICES**

WASH WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING. SHOWER DAILY AND CHANGE CLOTHES INCLUDING UNDERGARMENTS.

=====  
SECTION IX - DISCLAIMER  
=====**DISCLAIMER**

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURES BELIEVED BY THE SIMPSON COATINGS GROUP, INC. TO BE ACCURATE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS ACCURACY OR CORRECTNESS.